Nex.Station

More efficiency at the counter Simplify media processing and stock management



The Nex.Station Shielded stands for proven technology and discreet design to optimise everyday routine tasks and thus relieve the team. At the counter, the Nex.Station is standard equipment for every modern library. Integration into the library environment is seamless. The shielded antenna ensures exact detection of the media labels placed on it.

RFID speeds up the workflow for staff: RFID transponders can be read, written and initialised in seconds. Rapid batch booking is efficient. Even multi-part media packages are easily processed and checked for completeness.

Nexbib provides the latest software generation supporting various data models. A simple USB connection allows convenient movement within the library. It is compatible with all standard computers and barcode scanners in the library.



ANTENNA

DIMENSIONS (W x H x D)

- WEIGHT CHIP COMPATIBILITY IC-PROTOCOL FREQUENCY ITEM DETECTION ANTENNA CABLE MATERIALS READ RANGE HOUSING DESIGN OPTIONS
- 290 x 290 (+/-1 mm) x 18 mm without feet 290 x 290 (+/-1 mm) x 21 mm with feet 400 g SLIX, SLIX2, SLI-L, Tag-it ISO/IEC 15693 13.56 MHz 20+ simultaneously 2 m 50 Ohm Co-axial cable Composite Materials/Valchromat housing 250 mm Rounded, ergonomic Auto Power off Option Mounting below desk



RFID-READER

DIMENSIONS (W x H x D) WEIGHT TRANSMITTING POWER OPERATING TEMPERATURE ENCLOSURE POWER SUPPLY SUPPORTED TRANSPONDERS OTHERS 123 x 105 x 25 mm 200 g 0.25 – 1.5W ± 1 dB -25 °C up to 55 °C Aluminium Alloy 12V DCl ISO15693/18000-3/28560 Anti-collision function | 70 tags per second Noise detection and mitigation Short circuit and overheat protection RS232/RS485/Ethernet/USB Multi tag detection



STANDARD CONFORMITY

RADIO LICENSE

Europa: EN 300 330 USA: FCC 47 CFR Teil 15 Canada: IC RSS-GEN, RSS-210

EMV-SAFETY

Low Voltage: EN 60950 Humans Exposure EN 50364 CE, RoHS certified

SOFTWARE

Nex.Matic Staff Tool Software

Circulation and Conversion functions Intuitive multi language user interface AFI/EAS Update Multipart item support Keyboard wedge mode Barcode scanner/Keyboard input Windows 10, Windows 11 (32/64bit)



